Data Sheet


ltem

1. Product description:

Seamless impregnated fiber wheel

Dimensions (in):	5" x 2" x 5/8"-11
Dimensions (mm):	125 x 50 x 15.9- 11
Material:	Silicon Carbide
Specification:	S SF Verde W I
Max. rpm:	3,800
Grit:	Super Fine
Optimal RPM:	1,500





TENAZIT®

125 mm T =50 mm 15.9 mm - 11









Stainless

metals













1. Application

- · For excellent polishing and finishing of bronze, copper, brass, stainless steel, and carbon steel parts.
- · Seamless construction prevents marks on the overlap of polished surfaces.
- The impregnated fiber provides extended service life.
- Excellent for working on aluminum.
- Ideal for wide surface applications.
- · Leaves a continuous satin finish.

2. Operating instructions

- Can be used wet or dry.
- For use with a satin finishing sander.
- Mount the wheel and let it run idle for one minute to verify that it is not damaged.
- Do not apply excessive pressure or strike the workpiece.

3. Safety information

- Never exceed the maximum speed indicated on the label.
- Always use safety guards.
- · Always wear complete personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause serious injury.



4. Handling

- The initial inspection must be carried out in the original box. If there is visible evidence of damage to the packaging, the product should not be accepted.
- Handle the wheels carefully to prevent tearing or cracking. If a product breaks, loses a section, or shows signs of damage, it must not be mounted.

5. Storage

• Store the product on a flat surface at least 10 cm (4 in) above the ground, away from damp, cold, or hot surfaces, or any type of fluid.

The ideal storage conditions for these products are 40–50% relative humidity and a temperature between 15 °C and 29 °C (59 °F and 84 °F).

6. Packaging units

• 1 piece.