

Data Sheet

Item
3406




1. Product description:

Diamond fiber polishing pad


Dimensions (in):	10"
Dimensions (mm):	250
Specification:	D60 - Paso 1 (000)
Grit:	60
Step:	1 (000)



DDF



D = 250 mm



Step	Grit Size	Marking
No. 1	D60	000
No. 2	D120	00
No. 3	D220	0
No. 4	D400	1
No. 5	D800	2
No. 6	D1500	3



1. Application

- Step 1 of 6 for surface polishing. Designed for the removal of deep scratches on marble, ceramic, porcelain tile, gravel, concrete, and natural stone.
- Ideal pads for polishing and maintenance of floors and surface areas.
- Specially designed to achieve mechanical gloss.
- Depending on the desired gloss level, 1 to 6 steps may be used.
- Thanks to its diamond grain technology, it quickly removes scratches, stains, and "orange peel" surface effects.
- High flexibility.

2. Instrucciones de operación

- Suitable for dry use on concrete surfaces.
- Suitable for wet use.
- Use with random orbital polisher model 2539.
- Mount the pad and let it run free for one minute to ensure there are no issues.
- Do not apply excessive pressure or strike against the work material.
- Use on homogeneous, pre-treated surfaces.
- Do not expose the pad to sharp edges or corners.

3. Safety information

- Never exceed the maximum operating speed indicated on the label.
- Always wear complete personal protective equipment (gloves, hearing protection, mask, and safety glasses).
- Improper use may cause injury.

Polisher

4. Handling

- Initial inspection must be performed in the original packaging. If visible evidence of damage is present, the product must not be accepted.
- Handle pads with care to prevent tearing or cracking. If a pad shows breakage, section detachment, or suspected damage, it must not be mounted.

5. Storage

- Store pads in conditions free from moisture, dust, and dirt, preferably in their original packaging, and avoid prolonged exposure to hot, cold, or wet surfaces.

6. Packaging units

- 1 piece.

www.austromex.com.mx